



**DESCRIP :** PATENT

**TITLE :** Flame retardant resin compsn. - comprises thermoplastic resin, organopolysiloxane resin, phosphoric ester and metal hydroxide

**ASSIGNEE :** SHINETSU CHEM IND CO LTD

**PACODE :** SHIE

**ACCNNO :** 328924

**DATE :** 19931221

**ABSTRACT :** < BASIC> JP 05339510 A The flame retardant resin compsn. comprises of A) 100 pts.wt. of thermoplastic resin; (B) 1 to 50, pref. 5 to 10 pts.wt. of organopolysiloxane resin of formula (1) and having a molecular weight of 500 to 100,000 pref. 1,000 to 10,000; (C) 1 to 50, pref. 10 to 30 pts.wt. of phosphoric ester, and (D) 20 to 200, pref. 30 to 100 pts.wt. of metal hydroxide.  $\text{RaSi(OR')bO(4-a-b)/2}$  (1) R = opt. substd. monovalent hydrocarbon gp.; R = H or 1-4C opt. substd. monovalent hydrocarbon gp; a = 0.1 to 3.0, (pref. 0.1 to 2.0); b = 0.01 to 0.5, pref. 0.01 to 0.05. (A) is polyethylene, polypropylene, high impact polystyrene, polycarbonate, polyvinyl chloride, acrylonitrile-butadiene-styrene copolymer or acrylonitrile-styrene copolymer. (B) has a curing temp. of 100 to 300 deg.C/ (C) is triphenyl phosphate, tricresyl phosphate, cresylphenyl phosphate or polyphosphoric ester. (D) is aluminum trihydroxide or magnesium dihydroxide. ADVANTAGE - The flame retardant resin compsn. has high safety and does not generate toxic gas nor causes dripping in combustion. Dwg.0/0

**COPYRIGHT:** FOR INTERNAL USE ONLY - PORTIONS COPYRIGHT BY DERWENT INFORMATION LIMITED - 1994

**PNBASIC :** J05339510

**PRIORNO :** J92177397

**DATEPR :** 19920611

**EQUIVDOC :** **J05339510** J92177397 JPAT

**SUBJECTP :** Inhibitors/Poisons; Si-Resin; Cure; Si-OR/Si-Alkoxy

**LANG :** JAPANESE

**TYPE :** PTNT

**IPCODE :** C08K-003/22; C08K-005/521; C08L-101/00; C08L-083/04; C08L-101/00

**DPCODE :** A18; E11; A26

**MANUAL :** A06-A00B; A07-A03; A07-A04F; A08-F; A08-F03; A08-F05; E05-G08; E34-B02; E34-C02

**YEAR :** 1993  
**YEARPR :** 1992  
**COMMENT :** 94-031970/04 < XRAM> C94-01476  
**RDATEMD :** Oct 19, 2000  
**RDATENT :** Apr 30, 1994  
**SECCODE :** 0  
**UPDATER :** TDD

---